## Lubricating composition useful in hydraulic fluids

Publication number: CN1319126

**Publication date:** 

2001-10-24

Inventor:

KIYOSHI BABA YOSHIHARU HANYUDA (NL)

Applicant:

SHELL INT RESEARCH (NL)

Classification:

- international:

C10M141/10; C10M141/00; (IPC1-7); C10M141/10

- European:

C10M141/10

Application number: CN19998011128 19990818

Priority number(s): EP19980307320 19980910; JP19980234758 19980820

Also published as:



WO0011122 (A1 US6756346 (B1) ES2181471T (T3 DK1109882T (T3 CN1222593C (C

more >>

Report a data error he

Abstract not available for CN1319126

Abstract of corresponding document: WO0011122

A lubricating oil composition comprising (I) 100 pbw of a base oil, (II) an antiwear agent comprising (i) from 0.05 to 10 pbw of a phosphorothionate and from 0.01 to 1.0 pbw of an amine salt of phosphorus compound and/or (ii) from 0.05 to 10 pbw of a dithiophosphate, and (III) a rust preventing agent comprising from 0.01 to 1.0 pbw of an amide obtained by reacting a polyalkylene polyamine and a carboxylic acid having from 4 to 30 carbon atoms, and the use of such lubricating composition.

Data supplied from the esp@cenet database - Worldwide

## [19]中华人民共和国国家知识产权局

[51] Int. Cl<sup>7</sup>

C10M141/10

//(C10M141/10,13

3: 16,137: 08,

137: 10,137: 14), C10N40/08,30/02,

40/04,40/12,30/0

6,30/12

[11]公开号 CN 1319126A

## [12] 发明专利申请公开说明书

[21] 申请号 99811128.7

[43]公开日 2001年10月24日

[22]申请日 1999、8.18 [21]申请号 99811128.7 [30] 优先权

[32]1998.8.20 [33]JP [31]234758/1998

[32]1998.9.10 [33]EP[31]98307320.6

[86]国际申请 PCT/EP99/06094 1999.8.18

[87]国际公布 W000/11122 英 2000.3.2

[85]进入国家阶段日期 2001.3.20

[71]申请人 国际壳牌研究有限公司

地址 荷兰海牙

[72]发明人 马扬普治

羽生田清志

[74]专利代理机构 中国国际贸易促进委员会专利商标事务所 代理人 王 杰

权利要求书5页 说明书24页 附图页数0页

## [54] 发明名称 可用于液压液中的润滑油组合物 [57] 描纂

一种润滑油组合物,其中包括(I)100pbw 基础油,(II)抗磨剂,包括(i)0.05 至10pbw 硫代磷酸酯和0.01 至1.0pbw 磷化合物的胺盐和/或(ii)0.05 到10pbw 二硫代磷酸酯,和(豆)防锈剂,包括0.01 到1.0pbw 通过聚亚烷基多胺与具有4至30个碳原子的羧酸反应获得的酰胺,以及润滑油组合物的用途。

知识产权出版社出版

PP05-0046-00 CN-NH '08.8.15